This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

1		REVISIONS			
DE) (505		5.175	13.11777.4.1	
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
7		AS DRAWN BY CANAM.	9/11/2012	JAG	
8		CHANGED HOLE SIZE FOR HOLES A1-2, C1-2, H1, & K1 FOR A BETTER FIT.	10/29/2012	JAG	
9	14-0126	CH'D TITLE BLOCK WAS RED BARN IS DART. ADDED MACHINE ENGRAVE NOTE. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	8/13/2014	DPD	RW
10	15-0226	UPDATED HOLE TABLE WAS D2 IS L1. DELETED HOLES E1 & E2. CH'D DIM G1 WAS \emptyset .25052508 \blacktriangledown .300 IS \emptyset .25132522 \blacktriangledown .700. CH'D HOLE \blacktriangledown TO BE CALLED RROM SAME SURFACE; D1 WAS \blacktriangledown .070 +.003000 IS \blacktriangledown .540 +.003000, H WAS \blacktriangledown .075 +.003000 IS \blacktriangledown .760 +.003000 J1 WAS \blacktriangledown .120 +.003000 IS \blacktriangledown .750 +.003000 IS \blacktriangledown .720 +.003000 H WAS \blacktriangledown .100 +.003000 H WAS \blacktriangledown .100 +.003000 IS \blacktriangledown .720 +.005000 ADDED HOLE \blacktriangledown NOTE. DELETED UNNECESSARY DIMS SHEET 2. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.		DPD	JAG
11	11 17-0117 UPDATED TO NEW STANDARDS. CH'D DIM WAS Ø.177 THRU ALL L J Ø.1880+.0005/0000 ▼ .55 ISØ.177 THRU ALL L J Ø.1882+.0005/0000 ▼ .55. REMOVED DIM 1.125, 2.379. ADDED DIM 5/10/2017 SM 8.5150±.0004, 8.5150±.0004, 8.5150±.0004.				JAG

SIDE PLATE

C45-2-1

DATE 4/10/2003

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ± .5°
.X ± .01 SURFACES = 125/
1. BREAK ALL SHARP EDGES
.015 x 45° OR .015R
2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERRET DIM AND TOL PER
ASME Y14.5M-2009

USED ON MODEL

SHEET 1 OF 2

DWG NO.

MAT'L 7075-T6

SCALE


HEAT TREAT FINISH BLACK ANODIZE

DRAWN BY: CANAM CHECKED: RJC 05/10/2017 OPPS APPR: AA 05/17/2017
QA APPR: JL 05/17/2017
APPROVED: JAG 05/17/2017

1:2

SPEC MIL-A-8625, TYPE II, CLASS II

TAG	X LOC	Y LOC	SIZE	
A1	-7.390	4.430	Ø .177 THRU ALL	
A2			∟」∅ .1882 ^{+.0005} √ .55	
В1	-7.142	2.087		
B2	-3.818	5.913	Ø .3125 ^{+.0050} THRU ALL	
В3	-3.177	2.087		
B4	273	2.087		
C1	-6.989	5.695	Ø .500 ^{+.005} THRU ALL	
C2	.636	5.695		
DI	-6.977	213	ϕ .6250 $^{+.0005}_{0000}$ THRU ALL L_J ϕ .750 $\sqrt{}$.540 $^{+.003}_{000}$	
G1	-2.842	4.709	Ø .2522 .700	
Н1	-2.194	4.833	ϕ .8754 THRU ALL .8751 THRU ϕ 1.000 ψ .475 $_{000}^{+.003}$	
J1	000	.000	Ø 1.0000 ^{+.0005} THRU ALL □ Ø 1.125 ▼ .520 ^{+.003}	
K1	-3.582	4.734	Ø .625 ▼ .760 .9055 ▼ .720+.005 .9050 ▼ .720000	
L1	-5.550	2.326	ϕ .6250 $^{+.0005}_{0000}$ THRU ALL \Box ϕ .750 $\overline{\lor}$.470 $^{+.003}_{000}$	



ASSY ASSY B/O Part # UNIT Description Material B/O INFORMATION OR SPECIFICATIONS C45-2-1 1 SIDE PLATE 7075-T6

